




EXTRUDED ALUMINUM STATIONARY LOUVER
MIAMI-DADE QUALIFIED • FLORIDA PRODUCT APPROVED
HIGH VELOCITY WIND-DRIVEN RAIN RESISTANT
5" (127) DEEP • VERTICAL BLADE
MODEL: 1605WDVM


QUALIFICATIONS:

- Miami-Dade County NOA No. : 18-1217.04
- Florida Product Approval No. : 29667.2
- Tested in accordance with: TAS-100A (Wind-Driven Rain Test), TAS-201 (Large Missile Impact Test), TAS-202 (Uniform Static Air Pressure Test), TAS-203 (Cyclic Wind Pressure Loading Test).
- AMCA 500-L (Wind-Driven Rain, Water Penetration, Airflow).
- AMCA 540 (Wind-Borne Debris Impact Test [Enhanced "Level E" Protection]).
- AMCA 550 (High Velocity Wind-Driven Rain Resistance Test).
- Wind load rating +/- 130 PSF.



STANDARD CONSTRUCTION:

- FRAME:** 5" (127) deep, Type 6063-T6 extruded aluminum, .080" (2.03) nominal wall thickness. Integral downspouts and caulking slot provided.
- BLADES:** Type 6063-T6 extruded aluminum, .060" (1.52) nominal wall thickness, with reinforcing bosses.
- BLADE ANGLE:** Fixed at 45 degrees.
- BLADE SPACING:** Approximately 1 1/2" (38) on centers.
- BLADE SUPPORT:** 2.5" (64) strap every 60" (1524) or less in height.
- SCREEN:** 5/8" x .050 (16 x 1.3) expanded, flattened aluminum bird screen in removable frame, inside (rear) mount (adds approximately 3/8" [10] to louver depth).
- FINISH:** Mill.
- MINIMUM SIZE:** 12" W x 12" H (305 x 305).
- MAX. SINGLE SECTION SIZE:** 72" W x 120" H (1829 x 3048) or 120" W x 72" H (3048 x 1829). 63 sq. ft. (5.9 m²). Larger louvers will require field assembly of smaller sections.



- OA MAX. SIZE:** Unlimited Width x 120" H (3048).
- APPROXIMATE SHIPPING WEIGHT:** 5 lbs. per ft² (24.4 Kg per m²).

OPTIONS:

- BSSS** Type 304 S.S. Bird Screen.
- BSN** No Bird Screen.
- ISA** Aluminum Insect Screen.
- ISSS** Type 304 S.S. Insect Screen.
- ESI** Extended Sill.
- PASI** Sill Pan.
- Other: _____ .

OPTIONAL FINISHES:

- PC3** Powder Coat AAMA 2603. Color: _____ .
- PC4** High Performance Powder Coat AAMA 2604 (Equivalent to 50% Kynar®). Color: _____ .
- PC5** Fluoropolymer Powder Coat AAMA 2605 (Equivalent to 70% Kynar®). Color: _____ .
- PCC** Prime Coat.



SCHEDULE TYPE:

PROJECT:

ENGINEER:

CONTRACTOR:

Page 1 of 3
 Dimensions are in inches (mm).

DATE	B SERIES	SUPERSEDES	DRAWING NO.
5 - 29 - 19	1600M	NEW	1605WDVM



EXTRUDED ALUMINUM STATIONARY LOUVER
MIAMI-DADE QUALIFIED • FLORIDA PRODUCT APPROVED
HIGH VELOCITY WIND-DRIVEN RAIN RESISTANT
5" (127) DEEP • VERTICAL BLADE • PERFORMANCE DATA
MODEL: 1605WDVM

AIRFLOW/ WATER PENETRATION DATA
for 48" x 48" (1219 x 1219) Louver Size

Free Area %		55%
Free Area sq. ft. (sq. m.)		8.77 (0.82)
I N T A K E	Free Area Velocity at Point of Beginning Water Penetration at .01 oz./sq. ft. (3 ml/sq. m) (15 min. test duration)	1250 fpm (381 m/min.)*
	Air Volume at 1250 fpm	10,963 cfm (5174 l/s)
	Free Area Velocity	
	Pressure Drop @ 1000 fpm	.18 in. w.g. (45 Pa)

NOTE: To minimize water penetration when sizing intake louvers, select a Free Area Velocity that is **below** the beginning point of water penetration.*Maximum Free Area Velocity tested is 1250 fpm. Beginning point of water penetration for this model is above 1250 fpm.

WIND DRIVEN RAIN PERFORMANCE

Core Ventilation	0	110	196	280	399	499	590	703	783	894	984
Rate in fpm (m/s)	(0.00)	(0.56)	(0.99)	(1.42)	(2.02)	(2.53)	(3.00)	(3.57)	(3.98)	(4.54)	(5.00)
Free Area Ventilation	0	200	356	509	725	907	1073	1278	1424	1625	178
Rate in fpm (m/s)	(0.00)	(1.02)	(1.81)	(2.59)	(3.68)	(4.61)	(5.45)	(6.49)	(7.23)	(8.26)	(9.09)
Effectiveness Ratio (%)	100	100	100	100	100	100	100	100	100	100	100
Penetration Class	A	A	A	A	A	A	A	A	A	A	A

Test was based on a 39.375" x 39.375" (1.0 m x 1.0 m) core area louver tested at a rainfall rate of 3" per hour (76 mm/hour) with a wind velocity of **29 mph (13 m/s)**.


DISCHARGE LOSS COEFFICIENT CLASS (INTAKE): 2. (Discharge Loss Coefficient Classification is as follows: 1=0.4 and above, 2=0.3 to 0.399, 3 = 0.2 to 0.299, 4 = 0.199 and below.)

Core Ventilation	0	88	199	300	399	484	589	686	786	882	987
Rate in fpm (m/s)	(0.00)	(0.45)	(1.01)	(1.52)	(2.03)	(2.46)	(2.99)	(3.48)	(3.99)	(4.48)	(5.01)
Free Area Ventilation	0	160	362	545	725	880	1071	1247	1429	1604	1795
Rate in fpm (m/s)	(0.00)	(0.81)	(1.84)	(2.77)	(3.68)	(4.47)	(5.44)	(6.33)	(7.26)	(8.15)	(9.12)
Effectiveness Ratio (%)	100	100	100	100	100	100	100	100	100	100	100
Penetration Class	A	A	A	A	A	A	A	A	A	A	A

Test was based on a 39.375" x 39.375" (1.0 m x 1.0 m) core area louver tested at a rainfall rate of 8" per hour (203 mm/hour) with a wind velocity of **50 mph (22 m/s)**.

DISCHARGE LOSS COEFFICIENT CLASS (INTAKE): 2. (Discharge Loss Coefficient Classification is as follows: 1=0.4 and above, 2=0.3 to 0.399, 3 = 0.2 to 0.299, 4 = 0.199 and below.)

PRESSURE DROP




Air Velocity in Feet (Meters) Per Minute Through Free Area

Louver test size: 48" x 48" (1219 x 1219 mm).
 Standard air density @ 0.075 lbs/ft³.
 Tested to AMCA Fig. 5.5 – 6.5.



Safe-Air Dowco certifies the Model 1605WDVM shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. Seal applies to air performance, water penetration and wind driven rain performance ratings.



Safe-Air Dowco certifies that the 1605WDVM shown herein is approved to bear the AMCA Listing Label. The ratings shown are based on tests and procedures performed in accordance with AMCA publications and comply with the requirements of the AMCA Listing Label Program. The AMCA Listing Label applies to Wind Borne Debris Impact Resistant Louvers. The AMCA Listing Label applies to High Velocity Wind Driven Rain Resistant Louvers.


SCHEDULE TYPE:	Page 2 of 3			
PROJECT:	Dimensions are in inches (mm).			
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR:	5 - 29 - 19	1600M	NEW	1605WDVM



EXTRUDED ALUMINUM STATIONARY LOUVER
MIAMI-DADE QUALIFIED • FLORIDA PRODUCT APPROVED
HIGH VELOCITY WIND-DRIVEN RAIN RESISTANT
5" (127) DEEP • VERTICAL BLADE • PERFORMANCE DATA
MODEL: 1605WDVM

FREE AREA in Square Feet and Square Meters

		Width in Inches and Meters																		
		12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120
Height in Inches and Meters	12	0.25	0.46	0.67	0.88	1.09	1.30	1.51	1.72	1.93	2.14	2.35	2.56	2.77	2.98	3.19	3.40	3.61	3.82	4.03
	0.30	0.02	0.04	0.06	0.08	0.10	0.12	0.14	0.16	0.18	0.20	0.22	0.24	0.26	0.28	0.30	0.32	0.34	0.35	0.37
	18	0.44	0.82	1.20	1.58	1.96	2.33	2.71	3.09	3.47	3.85	4.22	4.60	4.98	5.36	5.74	6.11	6.49	6.87	7.25
	0.46	0.04	0.08	0.11	0.15	0.18	0.22	0.25	0.29	0.32	0.36	0.39	0.43	0.46	0.50	0.53	0.57	0.60	0.64	0.67
	24	0.64	1.19	1.73	2.28	2.83	3.37	3.92	4.46	5.01	5.56	6.10	6.65	7.19	7.74	8.29	8.83	9.38	9.92	10.47
	0.61	0.06	0.11	0.16	0.21	0.26	0.31	0.36	0.41	0.47	0.52	0.57	0.62	0.67	0.72	0.77	0.82	0.87	0.92	0.97
	30	0.84	1.55	2.27	2.98	3.70	4.41	5.12	5.84	6.55	7.27	7.98	8.69	9.41	10.12	10.84	11.55	12.26	12.98	13.69
	0.76	0.08	0.14	0.21	0.28	0.34	0.41	0.48	0.54	0.61	0.68	0.74	0.81	0.87	0.94	1.01	1.07	1.14	1.21	1.27
	36	1.04	1.92	2.80	3.68	4.57	5.45	6.33	7.21	8.09	8.98	9.86	10.74	11.62	12.5	13.39	14.27	15.15	16.03	16.91
	0.36	0.10	0.18	0.26	0.34	0.42	0.51	0.59	0.67	0.75	0.83	0.92	1.00	1.08	1.16	1.24	1.33	1.41	1.49	1.57
	42	1.24	2.29	3.34	4.39	5.44	6.49	7.54	8.59	9.64	10.69	11.74	12.79	13.84	14.89	15.94	16.99	18.04	19.09	20.14
	1.07	0.11	0.21	0.31	0.41	0.50	0.60	0.70	0.80	0.9	0.99	1.09	1.19	1.29	1.38	1.48	1.58	1.68	1.77	1.87
	48	1.43	2.65	3.87	5.09	6.31	7.52	8.77	9.96	11.18	12.4	13.61	14.83	16.05	17.27	18.49	19.70	20.92	22.14	23.36
	1.22	0.13	0.25	0.36	0.47	0.59	0.70	0.81	0.93	1.04	1.15	1.26	1.38	1.49	1.60	1.72	1.83	1.94	2.06	2.17
	54	1.63	3.02	4.40	5.79	7.17	8.56	9.95	11.33	12.72	14.1	15.49	16.88	18.26	19.65	21.03	22.42	23.81	25.19	26.58
	1.37	0.15	0.28	0.41	0.54	0.67	0.80	0.92	1.05	1.18	1.31	1.44	1.57	1.70	1.83	1.95	2.08	2.21	2.34	2.47
60	1.83	3.38	4.94	6.49	8.04	9.60	11.15	12.71	14.26	15.81	17.37	18.92	20.48	22.03	23.58	25.14	26.69	28.25	29.80	
1.52	0.17	0.31	0.46	0.60	0.75	0.89	1.04	1.18	1.32	1.47	1.61	1.76	1.90	2.05	2.19	2.34	2.48	2.62	2.77	
66	2.03	3.75	5.47	7.19	8.91	10.64	12.36	14.08	15.80	17.52	19.25	20.97	22.69	24.41	26.13	27.86	29.58	31.30	33.02	
1.68	0.19	0.35	0.51	0.67	0.83	0.99	1.15	1.31	1.47	1.63	1.79	1.95	2.11	2.27	2.43	2.59	2.75	2.91	3.07	
72	2.22	4.11	6.00	7.89	9.78	11.67	13.56	15.45	17.34	19.23	21.12	23.01	24.9	26.79	28.68	30.57	32.46	34.35	36.24	
1.83	0.21	0.38	0.56	0.73	0.91	1.08	1.26	1.44	1.61	1.79	1.96	2.14	2.31	2.49	2.66	2.84	3.02	3.19	3.37	
78	2.42	4.48	6.54	8.60	10.65	12.71	14.77	16.83	18.89	20.94	23.00									
1.98	0.22	0.42	0.61	0.80	0.99	1.18	1.37	1.56	1.75	1.95	2.14									
84	2.62	4.85	7.07	9.30	11.52	13.75	15.98	18.20	20.43	22.65	24.88									
2.13	0.24	0.45	0.66	0.86	1.07	1.28	1.48	1.69	1.90	2.10	2.31									
90	2.82	5.21	7.60	10.00	12.39	14.79	17.18	19.57	21.97	24.36	26.76									
2.29	0.26	0.48	0.71	0.93	1.15	1.37	1.60	1.82	2.04	2.26	2.49									
96	3.01	5.58	8.14	10.70	13.26	15.82	18.39	20.95	23.51	26.07	28.63									
2.44	0.28	0.52	0.76	0.99	1.23	1.47	1.71	1.95	2.18	2.42	2.66									
102	3.21	5.94	8.67	11.40	14.13	16.86	19.59	22.32	25.05	27.78	30.51									
2.59	0.30	0.55	0.81	1.06	1.31	1.57	1.82	2.07	2.33	2.58	2.83									
108	3.41	6.31	9.21	12.10	15.00	17.90	20.80	23.70	26.59	29.49	32.39									
2.74	0.32	0.59	0.86	1.12	1.39	1.66	1.93	2.20	2.47	2.74	3.01									
114	3.61	6.67	9.74	12.81	15.87	18.94	22.00	25.07	28.14	31.20	34.27									
2.90	0.34	0.62	0.90	1.19	1.47	1.76	2.04	2.33	2.61	2.90	3.18									
120	3.81	7.04	10.27	13.51	16.74	19.98	23.21	26.44	29.68	32.91	36.15									
3.05	0.35	0.65	0.95	1.25	1.56	1.86	2.16	2.46	2.76	3.06	3.36									



SCHEDULE TYPE:	
PROJECT:	
ENGINEER:	
CONTRACTOR:	

Page 3 of 3			
Dimensions are in inches (mm).			
DATE	B SERIES	SUPERSEDES	DRAWING NO.
5 - 29 - 19	1600M	NEW	1605WDVM